

Patent claims

- 10009636-12404  
Sub 17
1. An electric axial flow machine with an ironless disk-shaped rotor (1) which is arranged on a machine shaft (2) and has permanent magnets (11) which are embedded in a fiber- or fabric-reinforced plastic (12), and on both sides next to the rotor (1) in each case a stator (3, 4), characterized in that the permanent magnets (11) are each joined with a positive fit to the surrounding fiber- or fabric-reinforced plastic (12) and the latter, together with the permanent magnets (11) and the machine shaft (2), forms a dimensionally stable unit.
  2. The electric axial flow machine as claimed in claim 1, characterized in that a plurality of permanent magnets (11) are arranged in a circular manner around the machine shaft (2) and the fiber- or fabric-reinforced plastic (12), in particular a thermosetting material, extends between the permanent magnets (11) altogether over at least 10%, preferably between 15% and 20%, of the circle.
  3. The electric axial flow machine as claimed in claim 1 or 2, characterized in that the rotor (1) has on the outer circumference or in the vicinity of the outer circumference a stiffening band (13), which comprises preimpregnated fibrous material, which preferably contains glass, carbon or Kevlar fibers, and, for stiffening purposes, the rotor (1) is preferably formed such that it becomes thicker from the inside outward.
  4. The electric axial flow machine as claimed in one of claims 1 to 3, characterized in that it has means for determining the magnetic pole position of

Sub 10  
77  
Cred.

5. The electric axial flow machine as claimed in one of claims 1 to 4, characterized in that the fiber- or fabric-reinforced plastic (12) comprises an epoxy resin or an imide resin with glass fiber reinforcement and preferably, for better thermal expansion and thermal conductivity, additionally comprises mineral substances.
6. The electric axial flow machine as claimed in one of claims 1 to 5, characterized in that the permanent magnets (11) respectively comprise at least two separate magnet segments (111) next to one another in the circumferential direction, which are preferably joined by means of a metal adhesive.
7. The electric axial flow machine as claimed in one of claims 1 to 6, characterized in that the stators (3, 4) each comprise an annular yoke (31, 41), in which slots (32, 42) extending approximately radially from the inside outward have been made, through which slots multi-phase windings (33, 43) are led.
8. The electric axial flow machine as claimed in one of claims 1 to 7, characterized in that the permanent magnets (11) or the slots (32, 42) are transposed in the circumferential direction.

- ADD  
to (Abstract)  
Add >  
B6